

Port Sections Guide Port of Rotterdam



GUIDE	22-3-2022
Section	Waalhaven 2 HBR Boeipaal 23
Check	Check Waalhaven
Photo/Chart	69
Position (lat / lon)	51°53'.64N 004°26'.7E
UKC policy	See basin
alongside	
Tidal range	See basin
Range of water	See basin
densities	
Bottom type	See basin
Dredging regime	N/A
Free text	Break bulk regime. Zone D. STS tankers conform HVR 2020 art 5.5, 5.6, 5.7. and 6.2, 6.3. STS mineral oils not allowed. Bunkering via barge on both sides of the vessel. Cargo operations on both sides when enough space available and buoy 20-21 and 25 are free.

Manoeuvre	Arrival
UKC policy	See basin
Size restriction	Max. loa 165 meters. Distance between buoy and dolphin are 215 meter.
Tidal restriction	See basin
Wind restriction	For one vessel: Bft 6 (13,8 m/s), from 45 till 135 degrees from the port/starboard bow For two vessel: Bft 5 (10,7 m/s), from 45 till 135 degrees from the port/starboard bow If wind speed limits are exceeded: sufficient tugs in the side or shift to berth or sea. Wind speeds are measured on board the vessel
Visibility restriction	N/A N/A
Speed restriction Passing requirements	See basin
Tug use	See basin
Berthing requirements	The vessel should moor with her bow heading West due to limited room to buoy span 24 Anchor to be dropped on windward side. Sufficient tension on lines to submerge buoy halfway. At night switch on deck lights to show the outline of the vessel.
Free text option	N/A

Manoeuvre	Departure
UKC policy	See basin
Size restriction	See arrival
Tidal restriction	See basin
Wind restriction	See arrival
Visibility restriction	N/A
Speed restriction	N/A
Passing	See basin
requirements	
Tug use	See basin
Unberthing	N/A
requirements	

ORT SECTION OF THE PROPERTY OF	Port Sections Guide Port of Rotterdam 22-3-2022
Section	Waalhaven 2 HBR Boeipaal 23
Check	Check Waalhaven
Photo/Chart	69
Free text option	N/A