

## **Port Sections Guide**

## **Port of Rotterdam**



Section 3e Petroleumhaven buoy - dolphin 61
Check Check 3e Petroleumhaven
Photo/Chart 57

Position (lat / lon)	51°52'.65N 004°17'.6E
UKC policy	See basin
alongside	
Tidal range	See basin
Range of water	See basin
densities	
Bottom type	See basin
Dredging regime	N/A
Free text	Petroleum harbour safety regime. STS + Bunkering on southside of vessel. STS on north side of vessel only with persmission Harbour master. No STS gas. Only closed tank cleaning.

Manoeuvre	Arrival
UKC policy	See basin
Size restriction	Distance buoy - dolphin 235 meters. Max. loa 185 meters, max. beam 32,50 meters.
	Maximum loa of sea-vessels alongside: 125 meters.
Tidal restriction	See basin
Wind restriction	For one vessel: Bft 6 (13,8 m/s), from 45 till 135 degrees from the port/starboard bow
	For two vessel: Bft 5 (10,7 m/s), from 45 till 135 degrees from the port/starboard bow
	If wind speed limits are exceeded: sufficient tugs in the side or shift to berth or sea.
	Wind speeds are measured on board the vessel
Visibility restriction	N/A
Speed restriction	N/A
Passing	N/A
requirements	
Tug use	See basin
Berthing	The vessel should moor with her bow heading into the wind and make use of a minimum of 1
requirements	anchor if possible, to be dropped on windward side.
	However, if the loa of the vessel is more than 125 meters, bow must be heading East.
	When heading east position the stern closer to the dolphin than than the bow to the buoy.
	Sufficient tension on lines to submerge buoy halfway.
	At night switch on deck lights to show the outline of the vessel.
Free text option	N/A

Manoeuvre	Departure
UKC policy	See basin
Size restriction	See arrival
Tidal restriction	See basin
Wind restriction	See arrival
Visibility restriction	N/A
Speed restriction	N/A
Passing	N/A
requirements	
Tug use	N/A

