



# Port Sections Guide

## Port of Rotterdam



27-11-2023

<b>Section</b>	<b>Beneluxhaven - EBS - Buitenzijde noord en zuid</b>
<b>Check</b>	<b>Check Beneluxhaven</b>
<b>Photo/Chart</b>	<b>22</b>

<b>Position (lat / lon)</b>	In vicinity of: 51°57'.1N 004°07'.6E
<b>UKC policy alongside</b>	See basin
<b>Tidal range</b>	See basin
<b>Range of water densities</b>	See basin
<b>Bottom type</b>	See basin
<b>Dredging regime</b>	N/A
<b>Free text</b>	N/A

<b>Manoeuvre</b>	<b>Arrival</b>
<b>UKC policy</b>	See basin
<b>Size restriction</b>	max. loa at Southside 229 meter and Northside 229 meter, max. beam 32,50 meter. STS is possible. In case of Wind force < 8 Bft: max. beam 78 meter northside and southside; In case of Wind force ≥ Bft 8 mooring is allowed with a: Max. beam Northside: 61 meter Max. beam Southside: 69 meter
<b>Tidal restriction</b>	N/A
<b>Wind restriction</b>	
<b>Visibility restriction</b>	N/A
<b>Speed restriction</b>	N/A
<b>Passing requirements</b>	N/A
<b>Tug use</b>	See basin
<b>Berthing requirements</b>	Portside docking is preferred for a better mooring lay out.
<b>Free text option</b>	

<b>Manoeuvre</b>	<b>Departure</b>
<b>UKC policy</b>	See basin
<b>Size restriction</b>	See basin
<b>Tidal restriction</b>	N/A
<b>Wind restriction</b>	N/A
<b>Visibility restriction</b>	N/A
<b>Speed restriction</b>	N/A
<b>Passing requirements</b>	See arrival
<b>Tug use</b>	See basin
<b>Unberthing requirements</b>	N/A
<b>Free text option</b>	N/A